

# HOT ROLLED PLATES

AVAILABLE TO SPECN ASTM A -36 OR EQUIVALENT

BS 4360 GR 50 OR EQUIPMENT

ASTMA 516 GR 70 + ASME SA 516 GR 70

| Thickness<br>mm | kg/m <sup>2</sup> | Thickness<br>mm | kg/m <sup>2</sup> |
|-----------------|-------------------|-----------------|-------------------|
| 3.0             | 23.50             | 40              | 314.00            |
| 3.2             | 25.12             | 45              | 353.25            |
| 4.0             | 31.40             | 50              | 392.50            |
| 5.0             | 39.25             | 55              | 431.75            |
| 6.0             | 47.10             | 60              | 471.00            |
| 8.0             | 62.80             | 65              | 510.25            |
| 10.0            | 78.50             | 70              | 549.50            |
| 12.5            | 98.12             | 75              | 588.75            |
| 15.0            | 117.75            | 80              | 628.00            |
| 20.0            | 157.00            | 90              | 706.50            |
| 22.5            | 176.62            | 100             | 785.00            |
| 25.0            | 196.25            | 110             | 863.50            |
| 30.0            | 235.50            | 120             | 942.00            |
| 32.0            | 251.20            | 130             | 1020.50           |
| 35.0            | 274.75            | 150             | 1177.50           |